



<p>Motion Seq#</p>	<p>Certified Amending Motion: Accept Public Comment No. 20.</p>
<p>1917-4</p>	<p>Recommended Text if Motion Passes:</p> <p>6.17 Interior Surfaces. 6.17.1 The interior of the body shall be free of all sharp projections and sharp corners. 6.17.2* The finish of the entire patient compartment and exterior storage, including interiors of storage cabinets, shall be as follows: (1) Impervious to soap, water, body fluids, and disinfectants (2) Mildew resistant (3) Fire resistant in compliance with 49 CFR 571, FMVSS 302 (4) Able to be cleaned and disinfected 6.17.3 Countertop horizontal surface shall be seamless and impervious to contaminants. 6.17.4 All edges that meet vertical cabinets shall be sealed. 6.17.5 Countertop horizontal surfaces shall be surrounded by a lip of not less than ½ in. (12 mm) in height. 6.17.6 Interior surface materials shall meet the flammability requirements of FMVSS 302 as well as the following: (a) <u>They shall exhibit a flame spread index not exceeding 200 when tested in accordance with ASTM E84 or ANSI/UL 723. The smoke developed index shall not be limited.</u> (b) <u>They shall exhibit a radiant panel index not exceeding 200 when tested in accordance with ASTM E 162, Standard Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source.</u></p> <p><u>Also: add ASTM E84, UL 723 and ASTM E162 to Chapter 2 on referenced standards</u></p> <hr/> <p>Recommended Text if Motion Fails:</p> <p>6.17 Interior Surfaces. 6.17.1 The interior of the body shall be free of all sharp projections and sharp corners. 6.17.2* The finish of the entire patient compartment and exterior storage, including interiors of storage cabinets, shall be as follows: (1) Impervious to soap, water, body fluids, and disinfectants (2) Mildew resistant (3) Fire resistant in compliance with 49 CFR 571, FMVSS 302 (4) Able to be cleaned and disinfected 6.17.3 Countertop horizontal surface shall be seamless and impervious to contaminants. 6.17.4 All edges that meet vertical cabinets shall be sealed. 6.17.5 Countertop horizontal surfaces shall be surrounded by a lip of not less than 1/2 in. (12 mm) in height.</p>

