



RESEARCH FOUNDATION

RESEARCH FOR THE NFPA MISSION

Errata

Report:

Fire Safety Challenges of Tall Wood Buildings – Phase 2: Task 2 & 3 – Cross Laminated Timber Compartment Fire Tests

Author(s)

Joseph Su and Pier-Simon Lafrance National Research Council of Canada Ottawa, Ontario, Canada

Matthew Hoehler and Matthew Bundy National Institute of Standards and Technlogy Gaithersburg, MD USA

February 2018

Errata No.: FPRF-2018-01-01

Reference:

Erratum

This is to correct typos in the heat flux equation in Task 2&3 Report FPRF-2018-01 (i.e. NRC A1-010659.1). On page 40, the sign in front of the second term of the heat flux equation should be minus (not plus) and the units of heat flux are W/m^2 (not W). The corrected text should read:

The incident heat flux at the plate thermometer at step $i\left(\left|\dot{q}_{inc}''\right|^i$, in W/m²) is calculated using the measured temperature of the plate thermometer $(T_{PT}, \text{ in } K)$ and the gas temperature near the plate thermometer $(T_{aas}, \text{ in } K)$ as follows:

$$\left[\dot{q}_{inc}^{"}\right]^{i} = \sigma \left[T_{PT}^{4}\right]^{i} - \frac{(h + K_{PT})\left(\left[T_{gas}\right]^{i} - \left[T_{PT}\right]^{i}\right) - C_{PT} \frac{\left[T_{PT}\right]^{i+1} - \left[T_{PT}\right]^{i-1}}{\left[t\right]^{i+1} - \left[t\right]^{i-1}}}{\varepsilon_{PT}}$$

The published results in both the report and data sets for heat flux are correct and not affected by the typos in the body of the report.

Issue date: April 22, 2020

Phone: 617-984-7281

E-mail: <u>foundation@nfpa.org</u> Copyright © 2020 All Rights Reserved